



MITSUBOSHI Classical V-Belts for DIN2215/ISO4184

Table 1




Belt indication



Z-Section								
Belt No.	Inside length Li (mm)	Datum length Ld(mm)	Belt No.	Inside length Li (mm)	Datum length Ld(mm)	Belt No.	Inside length Li (mm)	Datum length Ld(mm)
Z 9	240	262	Z 36 1/2	925	947	Z 65	1650	1672
Z 10 1/2	265	287	Z 37	940	962	Z 66	1675	1697
Z 11	280	302	Z 37 1/2	950	972	Z 67	1700	1722
Z 11 1/2	290	312	Z 38	965	987	Z 68	1725	1747
Z 12 1/2	315	337	Z 38 1/2	975	997	Z 69	1750	1772
Z 13	340	362	Z 39	990	1012	Z 70	1775	1797
Z 14	355	377	Z 39 1/2	1000	1022	Z 71	1800	1822
Z 14 1/2	370	392	Z 40	1016	1038	Z 72	1830	1852
Z 15	380	402	Z 40 1/2	1030	1052	Z 73	1850	1872
Z 15 1/2	395	417	Z 41	1041	1063	Z 74	1880	1902
Z 16	405	427	Z 41 1/2	1050	1072	Z 75	1900	1922
Z 16 1/2	420	442	Z 42	1060	1082	Z 78	1975	1997
Z 17	430	452	Z 42 1/4	1075	1097	Z 79	2000	2022
Z 17 1/2	445	467	Z 42 1/2	1080	1102	Z 82	2083	2105
Z 18	460	482	Z 43	1090	1112	Z 83 1/2	2120	2142
Z 18 1/2	470	492	Z 43 1/4	1100	1122	Z 88	2240	2262
Z 19	480	502	Z 43 1/2	1105	1127	Z 90 1/2	2300	2322
Z 19 1/2	500	522	Z 44	1120	1142	Z 93	2360	2382
Z 19 3/4	510	532	Z 44 1/2	1130	1152	Z 98	2500	2522
Z 20	515	537	Z 45	1140	1162			
Z 20 1/2	525	547	Z 45 1/2	1150	1172			
Z 21	530	552	Z 46	1165	1187			
Z 21 1/2	550	572	Z 46 1/2	1180	1202			
Z 22	560	582	Z 47	1194	1216			
Z 22 1/2	575	597	Z 47 1/2	1215	1237			
Z 23	585	607	Z 48	1225	1247			
Z 23 1/2	600	622	Z 48 1/2	1230	1252			
Z 24	610	632	Z 49	1250	1272			
Z 24 1/2	620	642	Z 49 1/2	1260	1282			
Z 25	630	652	Z 50	1270	1292			
Z 25 1/2	650	672	Z 50 1/2	1280	1302			
Z 26	660	682	Z 51	1295	1317			
Z 26 1/2	670	692	Z 51 1/2	1310	1332			
Z 27	685	707	Z 52	1320	1342			
Z 27 1/2	700	722	Z 52 1/2	1330	1352			
Z 28	710	732	Z 53	1346	1368			
Z 28 1/2	725	747	Z 53 1/2	1360	1382			
Z 29	730	752	Z 54	1371	1393			
Z 29 1/2	750	772	Z 54 1/2	1385	1407			
Z 30	765	787	Z 55	1400	1422			
Z 30 1/2	775	797	Z 55 1/2	1410	1432			
Z 31	790	812	Z 56	1422	1444			
Z 31 1/2	800	822	Z 56 1/2	1435	1457			
Z 32	820	842	Z 57	1450	1472			
Z 32 1/2	825	847	Z 57 1/2	1460	1482			
Z 33	840	862	Z 58	1475	1497			
Z 33 1/2	850	872	Z 59	1500	1522			
Z 34	865	887	Z 60	1525	1547			
Z 34 1/2	875	897	Z 61	1550	1572			
Z 35	890	912	Z 62	1575	1597			
Z 35 1/2	900	922	Z 63	1600	1622			
Z 36	915	937	Z 64	1625	1647			

The datum length Ld according to ISO 4184 comply the pitch length Lw according to DIN 7753.

Available size for raw edge cogged belt ZX



Belt indication




A-Section

Belt No.	Inside length Li (mm)	Datum length Ld(mm)	Belt No.	Inside length Li (mm)	Datum length Ld(mm)	Belt No.	Inside length Li (mm)	Datum length Ld(mm)	Belt No.	Inside length Li (mm)	Datum length Ld(mm)
A 10	254	284	A 44	1120	1150	A 90	2286	2316	A 185	4700	4730
A 11	280	310	A 45	1143	1173	A 91	2310	2340	A 187	4750	4780
A 12	305	335	A 45 1/2	1150	1180	A 92	2337	2367	A 190	4825	4855
A 13	330	360	A 46	1168	1198	A 93	2360	2390	A 195	4950	4980
A 14	355	385	A 46 1/2	1180	1210	A 94	2388	2418	A 197	5000	5030
A 15	381	411	A 47	1200	1230	A 95	2413	2443	A 200	5080	5110
A 16	407	437	A 47 1/2	1215	1245	A 96	2438	2468	A 217	5512	5542
A 17	432	462	A 48	1220	1250	A 97	2464	2494			
A 18	457	487	A 48 1/2	1225	1255	A 98	2500	2530			
A 19	480	510	A 49	1250	1280	A 99	2515	2545			
A 20	508	538	A 50	1270	1300	A 100	2540	2570			
A 21	535	565	A 51	1300	1330	A 101	2565	2595			
A 22	560	590	A 52	1320	1350	A 102	2591	2621			
A 23	585	615	A 53	1350	1380	A 103	2616	2646			
A 23 1/2	600	630	A 54	1375	1405	A 104	2650	2680			
A 24	610	640	A 55	1400	1430	A 105	2667	2697			
A 25	630	660	A 56	1422	1452	A 106	2692	2722			
A 25 1/2	650	680	A 57	1450	1480	A 107	2725	2755			
A 26	660	690	A 58	1475	1505	A 108	2743	2773			
A 26 1/2	670	700	A 59	1500	1530	A 109	2769	2799			
A 27	686	716	A 60	1525	1555	A 110	2800	2830			
A 27 1/2	700	730	A 61	1550	1580	A 112	2845	2875			
A 28	710	740	A 62	1575	1605	A 113	2870	2900			
A 29	730	760	A 63	1600	1630	A 114	2896	2926			
A 29 1/2	750	780	A 64	1625	1655	A 115	2921	2951			
A 30	767	797	A 65	1650	1680	A 116	2946	2976			
A 31	787	817	A 66	1676	1706	A 118	3000	3030			
A 31 1/2	800	830	A 67	1700	1730	A 120	3048	3078			
A 32	813	843	A 68	1725	1755	A 122	3100	3130			
A 32 1/2	825	855	A 69	1750	1780	A 124	3150	3180			
A 33	838	868	A 70	1775	1805	A 126	3200	3230			
A 33 1/2	850	880	A 71	1800	1830	A 128	3250	3280			
A 34	864	894	A 72	1825	1855	A 130	3300	3330			
A 34 1/2	875	905	A 73	1854	1884	A 132	3350	3380			
A 35	889	919	A 74	1880	1910	A 134	3400	3430			
A 35 1/2	900	930	A 75	1900	1930	A 136	3454	3484			
A 36	914	944	A 76	1930	1960	A 138	3500	3530			
A 36 1/2	925	955	A 77	1956	1986	A 140	3550	3580			
A 37	940	970	A 78	1980	2010	A 144	3658	3688			
A 37 1/2	950	980	A 79	2000	2030	A 148	3750	3780			
A 38	965	995	A 80	2032	2062	A 150	3810	3840			
A 38 1/2	975	1005	A 81	2060	2090	A 153	3886	3916			
A 39	990	1020	A 82	2083	2113	A 155	3937	3967			
A 39 1/2	1000	1030	A 83	2110	2140	A 158	4000	4030			
A 40	1016	1046	A 83 1/2	2120	2150	A 162	4115	4145			
A 40 1/2	1030	1060	A 84	2134	2164	A 165	4200	4230			
A 41	1041	1071	A 84 1/2	2150	2180	A 167	4250	4280			
A 41 1/2	1050	1080	A 85	2160	2190	A 170	4318	4348			
A 42	1060	1090	A 86	2180	2210	A 173	4394	4424			
A 42 1/2	1075	1105	A 87	2210	2240	A 176	4470	4500			
A 43	1100	1130	A 88	2240	2270	A 177	4500	4530			
A 43 1/2	1105	1135	A 89	2260	2290	A 180	4572	4602			

The datum length Ld according to ISO 4184 comply the pitch length Lw according to DIN 7753.

: Available size for raw edge cogged belt AX

B/17, BX



Belt indication

B 59

Cross section

Belt No.(inch)



B-Section

Belt No.	Inside length Li (mm)	Datum length Ld(mm)	Belt No.	Inside length Li (mm)	Datum length Ld(mm)	Belt No.	Inside length Li (mm)	Datum length Ld(mm)	Belt No.	Inside length Li (mm)	Datum length Ld(mm)
B 22 1/2	570	613	B 52	1320	1363	B 99	2515	2558	B 180	4572	4615
B 23	585	628	B 52 1/2	1335	1378	B 100	2540	2588	B 185	4700	4743
B 24	615	658	B 53	1350	1393	B 101	2565	2608	B 187	4750	4793
B 25	630	673	B 53 1/2	1360	1403	B 102	2600	2643	B 190	4826	4869
B 25 1/2	650	693	B 54	1372	1415	B 103	2616	2659	B 193	4900	4943
B 26	660	703	B 55	1400	1443	B 104	2650	2693	B 195	4953	4996
B 26 1/2	670	713	B 56	1425	1468	B 105	2667	2710	B 197	5000	5043
B 27	686	729	B 57	1450	1493	B 106	2700	2743	B 200	5080	5123
B 28	710	759	B 58	1475	1518	B 107	2718	2761	B 204	5182	5225
B 28 1/2	725	768	B 59	1500	1543	B 108	2750	2793	B 208	5280	5323
B 29	735	778	B 60	1525	1568	B 109	2769	2812	B 210	5334	5377
B 29 1/2	750	793	B 61	1550	1593	B 110	2800	2843	B 211	5359	5402
B 30	762	805	B 62	1575	1618	B 112	2845	2888	B 216	5500	5543
B 30 1/2	775	818	B 63	1600	1643	B 113	2870	2913	B 220	5600	5643
B 31	785	828	B 64	1625	1668	B 114	2900	2943	B 224	5690	5733
B 31 1/2	800	848	B 65	1650	1693	B 115	2921	2964	B 225	5700	5743
B 32	813	856	B 66	1675	1718	B 116	2950	2993	B 226	5740	5783
B 32 1/2	825	868	B 67	1700	1743	B 117	2972	3015	B 232	5893	5936
B 33	838	881	B 68	1725	1768	B 118	3000	3043	B 236	6000	6043
B 33 1/2	850	893	B 69	1750	1793	B 120	3048	3091	B 238	6045	6088
B 34	865	908	B 70	1775	1818	B 122	3099	3142	B 240	6096	6139
B 34 1/2	875	918	B 71	1800	1843	B 124	3150	3193	B 248	6300	6343
B 35	889	932	B 72	1825	1868	B 125	3175	3218	B 256	6500	6543
B 35 1/2	900	943	B 73	1850	1893	B 126	3200	3243	B 260	6600	6643
B 36	915	958	B 74	1880	1923	B 128	3250	3293	B 264	6700	6743
B 36 1/2	925	968	B 75	1900	1943	B 130	3300	3343	B 268	6800	6843
B 37	940	983	B 76	1930	1973	B 132	3350	3393	B 272	6900	6943
B 37 1/2	950	993	B 77	1950	1993	B 133	3375	3418	B 276	7000	7043
B 38	965	1008	B 78	1981	2024	B 134	3400	3443	B 280	7100	7143
B 38 1/2	975	1018	B 79	2000	2043	B 135	3425	3468	B 295	7500	7543
B 39	991	1034	B 80	2032	2075	B 136	3450	3493	B 300	7620	7663
B 39 1/2	1000	1043	B 81	2060	2103	B 138	3500	3543	B 315	8000	8043
B 40	1016	1059	B 82	2083	2126	B 140	3550	3593			
B 40 1/2	1030	1073	B 83	2100	2143	B 142	3600	3643			
B 41	1040	1083	B 83 1/2	2120	2163	B 144	3658	3701			
B 41 1/2	1050	1093	B 84	2134	2177	B 146	3700	3743			
B 42	1060	1103	B 85	2160	2203	B 148	3750	3793			
B 42 1/2	1075	1118	B 86	2200	2243	B 150	3810	3853			
B 43	1090	1133	B 87	2210	2253	B 151	3850	3893			
B 43 1/2	1100	1143	B 88	2240	2283	B 152	3861	3904			
B 44	1120	1163	B 89	2260	2303	B 154	3912	3955			
B 45	1150	1190	B 90	2286	2329	B 155	3937	3980			
B 45 1/2	1163	1206	B 91	2300	2343	B 156	3950	3993			
B 46	1175	1218	B 92	2337	2380	B 158	4000	4043			
B 46 1/2	1180	1223	B 93	2360	2403	B 162	4115	4158			
B 47	1200	1243	B 94	2388	2431	B 164	4165	4208			
B 47 1/2	1207	1250	B 94 1/2	2400	2443	B 165	4200	4243			
B 48	1215	1258	B 95	2413	2456	B 167	4250	4293			
B 48 1/2	1225	1268	B 96	2438	2481	B 170	4318	4361			
B 49	1250	1293	B 96 1/2	2450	2493	B 173	4394	4437			
B 50	1275	1318	B 97	2465	2508	B 175	4450	4493			
B 51	1300	1343	B 98	2500	2543	B 177	4500	4543			

The datum length Ld according to ISO 4184 comply the pitch length Lw according to DIN 7753.

: Available size for raw edge cogged belt BX

Table 4



C-Section

Belt No.	Inside length Li (mm)	Datum length Ld(mm)	Belt No.	Inside length Li (mm)	Datum length Ld(mm)	Belt No.	Inside length Li (mm)	Datum length Ld(mm)
C 38	950	1002	C 92	2337	2389	C 167	4250	4302
C 39	975	1027	C 93	2360	2412	C 168	4267	4319
C 40	1000	1052	C 94	2388	2440	C 173	4390	4442
C 41	1030	1082	C 95	2413	2465	C 175	4445	4497
C 43	1090	1142	C 96	2438	2490	C 177	4500	4552
C 44	1120	1172	C 97	2465	2517	C 180	4572	4624
C 45	1150	1202	C 98	2500	2552	C 183	4648	4700
C 47	1200	1252	C 99	2525	2577	C 185	4700	4752
C 48	1220	1272	C 100	2540	2592	C 187	4750	4802
C 49	1250	1302	C 101	2560	2612	C 190	4825	4877
C 50	1270	1322	C 102	2591	2643	C 195	4950	5002
C 51	1295	1347	C 103	2616	2668	C 197	5000	5052
C 52	1320	1372	C 104	2642	2694	C 200	5080	5132
C 53	1350	1402	C 105	2667	2719	C 202	5131	5183
C 54	1375	1427	C 106	2692	2744	C 204	5182	5234
C 55	1400	1452	C 108	2750	2802	C 208	5300	5352
C 56	1425	1477	C 110	2800	2852	C 210	5334	5386
C 57	1450	1502	C 111	2819	2871	C 216	5486	5538
C 58	1475	1527	C 112	2845	2897	C 220	5600	5652
C 59	1500	1552	C 113	2870	2922	C 222	5639	5691
C 60	1525	1577	C 114	2896	2948	C 224	5690	5742
C 61	1550	1602	C 115	2921	2973	C 225	5715	5767
C 62	1575	1627	C 116	2950	3002	C 228	5791	5843
C 63	1600	1652	C 117	2965	3017	C 236	6000	6052
C 64	1625	1677	C 118	3000	3052	C 238	6045	6097
C 65	1650	1702	C 120	3050	3102	C 240	6096	6148
C 66	1675	1727	C 122	3100	3152	C 248	6300	6352
C 67	1700	1752	C 123	3125	3177	C 250	6350	6402
C 68	1725	1777	C 124	3150	3202	C 256	6500	6552
C 69	1750	1802	C 125	3175	3227	C 258	6553	6605
C 70	1775	1827	C 126	3200	3252	C 264	6700	6752
C 71	1800	1852	C 128	3250	3302	C 268	6800	6852
C 72	1829	1881	C 130	3300	3352	C 270	6858	6910
C 73	1854	1906	C 132	3350	3402	C 276	7010	7062
C 74	1880	1932	C 134	3400	3452	C 280	7100	7152
C 75	1900	1952	C 136	3450	3502	C 293	7442	7494
C 76	1930	1982	C 138	3500	3552	C 295	7500	7552
C 77	1956	2008	C 140	3550	3602	C 300	7600	7652
C 78	1981	2033	C 142	3600	3652	C 315	8000	8052
C 79	2000	2052	C 144	3658	3710	C 330	8380	8432
C 80	2032	2084	C 146	3700	3752	C 335	8500	8552
C 81	2060	2112	C 148	3750	3802	C 354	9000	9052
C 82	2083	2135	C 150	3810	3862	C 358	9093	9145
C 83	2108	2160	C 152	3861	3913	C 360	9144	9196
C 84	2135	2187	C 154	3912	3964	C 368	9347	9400
C 85	2159	2211	C 155	3937	3989	C 382	9700	9752
C 86	2184	2236	C 156	3962	4014	C 390	9906	9958
C 87	2210	2262	C 158	4000	4052	C 420	10668	10720
C 88	2240	2292	C 160	4064	4116			
C 89	2261	2313	C 162	4115	4167			
C 90	2286	2338	C 164	4166	4218			
C 91	2311	2363	C 166	4216	4274			

The datum length Ld according to ISO 4184 comply the pitch length Lw according to DIN 7753.

Available size for raw edge cogged belt CX

Table 5

D-Section						E-Section					
Belt No.	Inside length Li (mm)	Datum length Ld(mm)	Belt No.	Inside length Li (mm)	Datum length Ld(mm)	Belt No.	Inside length Li (mm)	Datum length Ld(mm)	Belt No.	Inside length Li (mm)	Datum length Ld(mm)
D 79	2000	2075	D 268	6800	6875	E 180	4575	4657			
D 86	2175	2250	D 270	6850	6925	E 197	5000	5082			
D 88	2240	2315	D 280	7100	7175	E 210	5300	5382			
D 90	2286	2361	D 285	7250	7325	E 220	5600	5682			
D 93	2360	2435	D 295	7500	7575	E 236	6000	6082			
D 95	2425	2500	D 298	7570	7645	E 240	6100	6182			
D 98	2500	2575	D 300	7620	7695	E 270	6850	6932			
D 102	2575	2650	D 315	8000	8075	E 300	7100	7182			
D 104	2650	2725	D 330	8380	8455	E 330	8380	8462			
D 105	2675	2750	D 335	8500	8575	E 360	9150	9232			
D 110	2800	2875	D 354	9000	9075	E 394	10000	10082			
D 115	2925	3000	D 358	9093	9168	E 420	10670	10752			
D 118	3000	3075	D 360	9144	9219	E 480	12190	12272			
D 120	3048	3123	D 374	9500	9575	E 540	13720	13802			
D 124	3150	3225	D 384	9750	9825	E 600	15240	15322			
D 126	3200	3275	D 390	9900	9975	E 630	16000	16082			
D 128	3250	3325	D 394	10000	10075	E 660	16760	16842			
D 132	3350	3425	D 418	10617	10692						
D 135	3425	3500	D 420	10670	10745						
D 140	3550	3625	D 440	11200	11275						
D 144	3658	3733	D 480	12190	12265						
D 148	3750	3825	D 492	12500	12575						
D 150	3810	3885	D 540	13720	13795						
D 155	3925	4000	D 550	14000	14075						
D 158	4000	4075	D 630	16000	16075						
D 162	4115	4190	D 660	16760	16835						
D 163	4150	4225									
D 167	4250	4325									
D 168	4267	4342									
D 173	4390	4465									
D 177	4500	4575									
D 180	4570	4645									
D 182	4620	4695									
D 187	4750	4825									
D 190	4825	4900									
D 195	4950	5025									
D 197	5000	5075									
D 200	5080	5155									
D 204	5180	5255									
D 209	5300	5375									
D 210	5330	5405									
D 214	5436	5511									
D 216	5500	5575									
D 220	5600	5675									
D 225	5715	5790									
D 228	5790	5865									
D 236	6000	6075									
D 238	6045	6120									
D 240	6096	6171									
D 248	6300	6375									
D 256	6500	6575									
D 264	6700	6775									

The datum length Ld according to ISO 4184 comply the pitch length Lw according to DIN 7753.

Cross-section Dimension for MITSUBOSHI Classical V-belts

Table 6

Section	ISO 4184 DIN 2215	Z 10	A 13	B 17	C 22	D 32	E 40
Top belt width	b_o (mm)	10	13	17	22	32	40
Datum width	b_d (mm)	8.5	11	14	19	27	32
Height of belts	h (mm)	6	8	11	14	20	25
Datum belt length	$L_d \approx L_i +$ (mm)	22	30	43	52	75	82
Distance down to datum line	h_d (mm)	2.5	3.3	4.2	5.7	8.1	12
Outside belt length	$L_a \approx L_i +$ (mm)	38	50	69	88	126	157
Recommended minimum pulley datum diameter	dd (mm)	45 (40)	71 (63)	112 (90)	180 (140)	315	450
Recommended maximum belt speed	V (m/s)	30					

() : Figure of recommended minimum pulley datum diameter for raw edge cogged type.





Fig. 8

Maxtar Wedge V-belts for RMA/MPTA

Table 7



Section	bo (mm)	h (mm)
3V/9N (3VX)	9.5	8.0
5V/15N (5VX)	16.0	13.5
8V/25N	25.5	23.0

Belt indication

5V 1000

Cross section

Belt No. (inch×10)

3V(3VX)-Section			5V(5VX)-Section			8V-Section		
Belt No.	Effective outside length La(mm)	Datum length Ld(mm)	Belt No.	Effective outside length La(mm)	Datum length Ld(mm)	Belt No.	Effective outside length La(mm)	Datum length Ld(mm)
3V 250	635	631	5V 500	1270	1262	8V 1000	2540	2524
3V 265	673	669	5V 530	1346	1338	8V 1060	2692	2676
3V 280	711	707	5V 560	1422	1414	8V 1120	2845	2829
3V 300	762	758	5V 600	1524	1516	8V 1180	2997	2981
3V 315	800	796	5V 630	1600	1592	8V 1250	3175	3159
3V 335	851	847	5V 670	1702	1694	8V 1320	3353	3337
3V 355	902	898	5V 710	1803	1795	8V 1400	3556	3540
3V 375	953	949	5V 750	1905	1897	8V 1500	3810	3794
3V 400	1016	1012	5V 800	2032	2024	8V 1600	4064	4048
3V 425	1080	1076	5V 850	2159	2151	8V 1700	4318	4302
3V 450	1143	1139	5V 900	2286	2278	8V 1800	4572	4556
3V 475	1207	1203	5V 950	2413	2405	8V 1900	4826	4810
3V 500	1270	1266	5V 1000	2540	2532	8V 2000	5080	5064
3V 530	1346	1342	5V 1060	2692	2684	8V 2120	5385	5369
3V 560	1422	1418	5V 1120	2845	2837	8V 2240	5690	5674
3V 600	1524	1520	5V 1180	2997	2989	8V 2360	5994	5978
3V 630	1600	1596	5V 1250	3175	3167	8V 2500	6350	6334
3V 670	1702	1698	5V 1320	3353	3345	8V 2650	6731	6715
3V 710	1803	1799	5V 1400	3556	3548	8V 2800	7112	7096
3V 750	1905	1901	5V 1500	3810	3802	8V 3000	7620	7604
3V 800	2032	2028	5V 1600	4064	4056	8V 3150	8001	7985
3V 850	2159	2155	5V 1700	4318	4310	8V 3350	8509	8493
3V 900	2286	2282	5V 1800	4572	4564	8V 3550	9017	9001
3V 950	2413	2409	5V 1900	4826	4818	8V 3750	9525	9509
3V 1000	2540	2536	5V 2000	5080	5072	8V 4000	10160	10144
3V 1060	2692	2688	5V 2120	5385	5377	8V 4250	10795	10779
3V 1120	2845	2841	5V 2240	5690	5682	8V 4500	11430	11414
3V 1180	2997	2993	5V 2360	5994	5986	8V 4750	12065	12049
3V 1250	3175	3171	5V 2500	6350	6342	8V 5000	12700	12684
3V 1320	3353	3349	5V 2650	6731	6723	8V 5600	14224	14208
3V 1400	3556	3552	5V 2800	7112	7104			
			5V 3000	7620	7612			
			5V 3150	8001	7993			
			5V 3350	8509	8501			
			5V 3550	9017	9009			

Available size for raw edge cogged belt 3VX & 5VX